List of activities for which accreditation has been terminated

(Notification Letter No. HOKLAS104-107; Effective date of termination: 25 July 2024)

A.E.S. Destructive and Non-Destructive Testing Limited

安捷材料試驗有限公司

	Calibration Services 校正服務	
ITEM TESTED OR MEASURED 測試或量度項目	SPECIFIC TEST OR PROPERTY MEASURED [@] 特定測試或量度的特性 [@]	CALIBRATION AND MEASUREMENT CAPABILITY (CMC)* 校準和測量能力*
Th	ne accreditation of the following calibrations has been	terminated
Construction materials testing equipment		
- Welding gauge calibrator set	Calibration in accordance with in-house method OP-54 for the following parameters :	
	Scale measuring step wedge: 1 mm to 25 mm Scale measuring angle wedge: 20° to 90°	20 μm 0.2°
Length and related quantities		
- Length		
- Extensometer		
- Class B-1, B-2, C, D and E for gauge length from 25 mm to 200 mm	On-site calibration for displacement using calibration rig and verification of class in accordance with ASTM E83: 2016 over the following range:	
	0.035 mm to 2.8 mm	1.6 μm

[®] Unless otherwise specified, accredited activities are conducted at the laboratory.

^{*} The calibration uncertainty of a device under test, which is usually reported at 95% confidence level, depends on both the CMC of the laboratory and the performance of the device during calibration.

List of activities for which accreditation has been terminated

(Notification Letter No. HOKLAS104-107; Effective date of termination: 25 July 2024)

A.E.S. Destructive and Non-Destructive Testing Limited

安捷材料試驗有限公司

Flat F, 2/F, Block 2, Kwai Tak Industrial Centre, 15-33 Kwai Tak Street, Kwai Chung, New Territories, Hong Kong 香港新界蒸涌蒸汽港 15-33 蒸汽工 堂中心第二座二字樓 F

Construction Materials 建築材料			
ITEM TESTED OR MEASURED 測試或量度項目	SPECIFIC TEST OR PROPERTY MEASURED 特定測試或量度的特性	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED 規範、標準方法或應用技術	
	The accreditation of the following tests has been	terminated	
Structural fixings (fixing components)	Tensile proof load test of anchor bolts, cast-in fixings and channel inserts up to 1000 kN	BS 5080: Part 1: 1993 Cl. 6, 7.1.1 & 7.1.3 with modifications (by incremental loading) In-house method OP-16	
	Tightening torque test of anchor bolts up to 1000 Nm	In-house method OP-79	
	Tightening torque control method of fastener/nut assemblies up to 1000 kN	BS 4604-1: 1970 Cl. 4.3 BS 4604-2: 1970 Cl. 4.2	

List of activities for which accreditation has been terminated

(Notification Letter No. HOKLAS104-103; Effective date of termination: 14 June 2022)

A.E.S. Destructive and Non-Destructive Testing Limited

安捷材料試驗有限公司

Unless otherwise specified, accredited activities are conducted at the laboratory.

^{*} The calibration uncertainty of a device under test, which is usually reported at 95% confidence level, depends on both the CMC of the laboratory and the performance of the device during calibration.

List of activities for which accreditation has been terminated

(Notification Letter No. HOKLAS104-101; Effective date of termination: 10 February 2022)

A.E.S. Destructive and Non-Destructive Testing Limited

安捷材料試驗有限公司

Calibration Services 校正服務			
ITEM TESTED OR MEASURED 測試或量度項目	SPECIFIC TEST OR PROPERTY MEASURED [®] 特定測試或量度的特性 [®]	CALIBRATION AND MEASUREMENT CAPABILITY (CMC)* 校準和測量能力*	
	Accreditation for the following tests has been	terminated.	
Length and related quantities			
- Length			
- Dial gauge	Calibration using micrometer head in accordance with Cl. B3 of BS 907: 1965 or Cl. A5 of AS 2103: 1978 over the following range: Up to 50 mm	4.9 μm	
- External micrometer	Calibration in accordance with App. A of BS 870: 1950 over the following range: Up to 25 mm	2 μm	
	Op to 23 min	2 μπ	
- Extensometer	On-site calibration in accordance with ISO 9513: 1999 using calibration rig for the following:		
	Class 1 for gauge length Up to 200 mm	0.8 μm	
	On-site calibration in accordance with ASTM E83: 2002 using calibration rig for the following:		
	Class B-1, B-2, C, D and E for gauge length Up to 200 mm	0.8 μm	

[®] Unless otherwise specified, accredited activities are conducted at the laboratory.

^{*} The calibration uncertainty of a device under test, which is usually reported at 95% confidence level, depends on both the CMC of the laboratory and the performance of the device during calibration.

List of activities for which accreditation has been terminated

(Notification Letter No. HOKLAS104-101; Effective date of termination: 10 February 2022)

A.E.S. Destructive and Non-Destructive Testing Limited

安捷材料試驗有限公司

Calibration Services 校正服務		
ITEM TESTED OR MEASURED 測試或量度項目	SPECIFIC TEST OR PROPERTY MEASURED [@] 特定測試或量度的特性 [@]	CALIBRATION AND MEASUREMENT CAPABILITY (CMC)* 校準和測量能力*
	Accreditation for the following tests has been	terminated.
Mass and related quantities		
- Force measurements		
- Universal testing machine in compression mode	On-site calibration using follow-the-force method or set-the-force method in accordance with ASTM E4: 2002 over the following range: 0.4 kN to 3000 kN	0.3% (Calibration is conducted using elastic calibration devices)
- Hardness	On-site indirect verification for measuring Rockwell hardness in accordance with	
- Hardness testing machine	BS EN ISO 6508-2: 1999 over the following hardness ranges:	
	20 HRC to 30 HRC 35 HRC to 55 HRC 60 HRC to 70 HRC	1.1 HRC 1.1 HRC 1.1 HRC
- Torque		
- Manually operated torque wrench	Calibration in accordance with BS EN 26789: 1994, ISO 6789: 1992 or in-house method OP-2 over the following ranges :	
	from 1 Nm to 20 Nm from 20 Nm to 100 Nm from 100 Nm to 1000 Nm	0.24 Nm 1 % of reading 0.58 % of reading

[@] Unless otherwise specified, accredited activities are conducted at the laboratory.

^{*} The calibration uncertainty of a device under test, which is usually reported at 95% confidence level, depends on both the CMC of the laboratory and the performance of the device during calibration.

List of activities for which accreditation has been terminated

(Notification Letter No. HOKLAS104-89; Effective date of termination: 20 February 2017)

A.E.S. Destructive and Non-Destructive Testing Limited

安捷材料試驗有限公司

Flat F, 2/F, Block 2, Kwai Tak Industrial Centre, 15-33 Kwai Tak Street, Kwai Chung, New Territories, Hong Kong 香港新界葵涌葵德街 15-33 葵德工業中心第二座二字樓 F

Construction Materials 建築材料			
ITEM TESTED OR MEASURED 測試或量度項目	SPECIFIC TEST OR PROPERTY MEASURED 特定測試或量度的特性	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED 規範、標準方法或應用技術	
The accreditation of the following tests has been terminated.			
Metallic materials	Hardness test of metallic materials – Rockwell hardness test – HRC	BS EN ISO 6508-1: 1999	

List of activities for which accreditation has been terminated

(Notification Letter: 104-66)

.TEST .CATEGORY .測試類別	ITEMS, MATERIALS OR PRODUCTS TESTED 測試項目、材料或產品	SPECIFIC TESTS OR PROPERTIES MEASURED .特定測試或量度的特性	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED . 規範、標準方法或應用技術
CONSTRUCTION MATERIALS 建築材料	Metallic materials	Axial tensile test, wedge tensile test and proof load test of fasteners in the force range of 1.1 kN to 1500 kN	BS EN ISO 898-1 : 1999 Cl. 8.1, 8.2, 8.5 & 8.6 BS EN ISO 3506-1 : 1998 Cl. 6.2.2 to 6.2.4 & 6.2.6
	Welds (destructive)	Tensile test on welds in metallic materials in the force range 1.1 kN – 1500 kN	BS 709: 1983
		Bend test on welds in metallic materials	BS 709: 1983
		Charpy V-notch impact test on welds in metallic materials	BS 709: 1983
		Vickers hardness test on welds in metallic materials in the scale of HV 5, HV 10	BS 709: 1983
		Macroscopic examination on welds in metallic materials	BS 709: 1983

Note:

 $1. \ \, \text{The above tests have been voluntarily terminated with effect from 20 March 2014}.$

List of activities for which accreditation has been terminated

(Notification Letter: 104-65)

.TEST .CATEGORY .測試類別	ITEMS, MATERIALS OR PRODUCTS TESTED 測試項目、材料或產品	SPECIFIC TESTS OR PROPERTIES MEASURED .特定測試或量度的特性	CALIBRATION AND MEASUREMENT CAPABILITY* .校準和測量能力*
CALIBRATION SERVICES 校正服務	Mechanical metrology measurements (cont'd) - Dimensional measurements - Foil - Height gauge	Calibration of foil thickness in accordance with in-house method OP-75 over the following ranges: Up to 14 μm Above 14 μm to 25 μm Above 25 μm to 1500 μm Measurement of deviation of reading of height gauge (vernier and electronic) in accordance with Cl. A2 of BS 1643: 1983 over the following range:	1.6% 2.4% 1.6% ±5.8 µm
		Up to 300 mm	

Note

1. The above tests have been voluntarily terminated with effect from 27 February 2014.

Annex III (cont'd)

List of activities for which accreditation has been terminated

(Notification Letter: 104-65)

.TEST .CATEGORY	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED
测試類別	测試項目、材料或產品	特定測試或量度的特性	規範、標準方法或應用技術
CONSTRUCTION	141111111111111111111111111111111111111	W.C.A. W.L.Z.WII	7546 1817 17 181 1815 1815
MATERIALS	Metallic materials	Axial tensile strength test of fasteners	BS 3692: 1967 App. D.1 & D.2
建築材料		in the force range of 1.1 kN to 1500 kN	BS 4190: 1967 App. A.1 & A.2
		-	BS EN 20898-1: 1992 Cl. 8.1 & 8.2
		Axial tensile test, wedge tensile test and	BS 3692: 1967 App. D.6 & D.7
		proof load test of fasteners in the force	BS 4190: 1967 App. A.6 & A.7
		range of 1.1 kN to 1500 kN	BS 4395: Part 1: 1969 App. B.1, B.5 & B.6
			BS 4395: Part 2: 1969 App. B.1, B.5 & B.6
			BS 4395: Part 3: 1973 App. A.1, A.5 & A.6
			BS 6105: 1981 Cl. 6.2 to 6.4
			BS EN 20898-1: 1992 Cl. 8.4 & 8.5
		Proof load test of nuts in the force range of	BS 3692: 1967 App. E.1
		1.1 kN to 1500 kN	BS 4190: 1967 App. B.1
			BS 4395: Part 1: 1969 App. C.1
			BS 4395: Part 2: 1969 App. C.1
			BS 4395: Part 3: 1973 App. C.1
			BS 6105: 1981 Cl. 6.6
		Tensile test of weldable structural steel sections in the force range of 1.1 kN to 1500 kN	BS 4360: 1986

Note:

2. The above tests have been voluntarily terminated with effect from 27 February 2014.